Trade Waste Bylaw 2015

Description of Trade Waste and Premises General premises (1.10) Appendix B



6-8 Brougham Street, PO Box 21, Westport 7866

Phone 03 788 9111

Email info@bdc.govt.nz www.bullerdc.govt.nz

General premises (1.10)	www.bullerdc.govt.
Name of premises:	
Physical address:	
Postal address:	
Email:	
Telephone (day):	Mobile:
Telephone (after hours):	Fax:
Owner details	
Name of owner of premises:	
Postal address:	
Email:	
Telephone (day):	Mobile:
Telephone (after hours):	Fax:

Contact details for further enquiries

Name of owner of premises:		
Postal address:		
Email:		
Telephone (day):	Mobile:	
Telephone (after hours):	Fax:	
Total volume of wastes		
Average daily volume:		m³
Maximum volume in any 8 hour period:		m³
Maximum daily volume:		m³
Maximum flow:		m³
Seasonal fluctuation: (range)		I/sec
General characteristics of wastes		
Temperature (°C)	PH	
Typical:	Typical:	
Range:	Range:	
cBOD ⁵ (g/m³)	Oil and Grease (g/m³)	
Typical:	Typical:	
Range:	Range:	
COD (g/m³) Typical:	Enteroccoci (cfu/100ml) Typical:	
Range:	Range:	
Suspended Solids (g/m³) Typical:		
Range:		

The source of water used on the premises is

(a) from the Buller District Council	m³ / working day
(b) from other sources (state source)	m ³ / working day
The wastes do contain condensing water or stormwater and the layout of the drains on the such as to reasonably exclude the possibility of such becoming mixed with trade wastes. It is proposed that domestic wastewater and trade wastes should be discharges at the same of discharge.	•
Proposed method for flow measurement is	
A permanent installation of suitable flow measuring equipment	
Based on water usage as measured by meter	
Other	
Specify:	
List any substances contained in Schedule 1A or 1B of the bylaw that are st used, or generated on the premises.	
Describe mitigating measure employed to prevent accidental spillages of t substances from entering the public sewer or stormwater system.	hese

Site plans of the premises are attached	clearly showing the location
of the following as appropriate	
Process areas devices	Emergency spill
Trade waste drains devices	Stormwater drains
Domestic wastewater drains	Open areas draining to trade waste drains
Emergency spill containment	Other
Flow measures	Specify:
Main trade waste pretreatment systems	
Screens	pH Control
Flow balance	Grease traps
Chemical treatment	Biological treatment
Detailed drawings and descriptions for t	the following are attached as appropriate
Pretreatment systems	Flow measuring devices
Emergency spill containment	Sampling points
Method of flow meter calibration	
An independent waste audit of the premises has ,	/ has not been carried out by:

A discharge management plan is attached:

Council staff entering the premises are as follows:	
Process	
Use a separate page for each process and attach copies of typical analysis for wastew from each separate process.	ater
Process name and description:	
Type of product processed:	
Average daily volume:	m³
Maximum flow:	I /sec
Volume of wastewater	
Average daily volume:	m³
Maximum flow:	I /sec
If batch discharges	
Quantity	m³
Frequency: (hour/day/week)	
Rate of discharge:	I/sec
The wastewater contains the following characteristics, which when mixed with other discharged from the premises, or neat or in excess of the limits stipulated in schedule	
NOTE: The characteristics in table 1A.2 and table 1A.3 have a limit of zero unless approval for that particular	ar characteristic is applied for.

Value or concentration

	From	process	At point o	of discharge
	Typical	Maximum	Typical	Maximum
The following steps have been / will be taken to improve the to	ade proces	s as part of a	strategy	
of cleaner production.				

Important Note: Not all of the sections in this application may apply o your application to discharge trade waste. If you require assistance in completing this application, please contact the Council's 3 Waters Department.